

N 90, Telescopic cooker hood, 90 cm, Stainless steel
D49PU54X1B




COOKING PASSION SINCE 1877



Telescopic hood: designed to provide powerful extraction without impacting on your kitchen space or design. These hoods pull out from underneath a cabinet when required for a streamlined kitchen.

- ✓ Oven fit: bring harmony to your kitchen
- ✓ Automatic Air Sensor – automatically adjusts the extraction rate to match the situation in the kitchen
- ✓ EfficientDrive: save energy and enjoy a quieter kitchen thanks to efficient brushless motor technology
- ✓ TouchControl: thanks to the integrated flat surface of the control panel, adjustments can be easily made with just one finger
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense

B



Features

Technical Data

Typology : Pull-out
 Approval certificates : CE, VDE
 Length of electrical supply cord (cm) : 175
 Required niche size for installation (HxWxD) : 385mm x 524.0mm x 290mm
 Minimum distance above an electric hob : 430
 Minimum distance above a gas hob : 650
 Net weight (kg) : 14.431
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction (m³/h) : 395
 Boost position output recirculating (m³/h) : 641
 Maximum output recirculating air (m³/h) : 358
 Boost position air extraction (m³/h) : 700
 Number of lights (Stck) : 3
 Noise level (dB(A) re 1 pW) : 53
 Diameter of air outlet (mm) : 120 / 150
 Grease filter material : Washable stainless steel
 EAN code : 4242004251224
 Connection rating (W) : 146
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 50; 60
 Plug type : GB plug
 Installation type : Built-in

Optional accessories

Z51ITD1X1	Long Life recirculation kit external
Z51ITPOX0	
Z51IXB1X6	Clean Air Plus odor filter (replacement)
Z51IXC1X6	Clean Air Plus recirc. kit external
Z54TC02X0	Standard odor filter (replacement)
Z54TL90X1	Lowering frame
Z54TM90X0	Installation kit for 90cm wide wall unit
Z54TS02X0	Standard recirculation kit



4 242004 251224

N 90, Telescopic cooker hood, 90 cm, Stainless steel
D49PU54X1B



COOKING PASSION SINCE 1877

Features

Features

- ClimateControl sensor
- Touch control with 7 segment LED display
- 3 power levels and 2 intensive settings
- SoftLight with dimmer function
- 3 x 1,5W LED
- Efficient BLDC technology
- Noise reduction function
- Interval operation
- Automatic intensive revert (6mins)
- Automatic after running (Automatic after running (10 minutes))
- 3 metal grease filter cassettes
- Saturation indicator for metal and charcoal filter

Design

- 90 cm wide
- Stainless steel
- Handle strip specification: N6-design with logo
- Steel filter cover

Performance

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 395 m³/h
Intensive 700 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 53 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 53 dB(A) re 1 pW
Intensive: 69 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
Extraction rate in recirculation mode:
Max. normal use: 358 m³/h
Intensive: 641 m³/h
Noise level in recirculation mode:
Max. normal use: 60 dB(A) re 1 pW
Intensive: 71 dB(A) re 1 pW
- Colour Temperature: 3500 K
- Light Intensity: 355 lux
- Average Energy Consumption: 38.8 kWh/year*
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Power rating: 146 W







Planning and installation information

- Installation system: Telescopic comfort installat.
- Dimensions (HxWxD): 426 x 898 x 290 mm
- Built-in dimensions (HxWxD): 385 x 524 x 290 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Electrical cable length 1.75 m

* In accordance with the EU-Regulation No 65/2014

N 90, Telescopic cooker hood, 90 cm, Stainless steel
D49PU54X1B

Dimensioned drawings



N 90, Telescopic cooker hood, 90 cm, Stainless steel
D49PU54X1B

Dimensioned drawings

