

# Serie | 2, Telescopic cooker hood, 60 cm, Silver metallic DFM063W56B







#### **Optional accessories**

DSZ4545 : Standard recirculation kit

DSZ4551 : Standard odor filter (replacement)

# Telescopic cooker hoods extend when in use and slide neatly away when not in operation.

- Silent: maximum extractor performance with minimal noise.
- **LED Illumination:** The energy-saving lighting provides bright and clear lighting for the hob area.
- An impressive extraction rate of m3/h ensures this hood will have your kitchen odour free in no time.
- Beautifully designed to provide excellent viewability when not in use

#### **Technical Data**

Typology: Pull-out
Approval certificates: CE, VDE
Length of electrical supply cord (cm): 175

Required niche size for installation (HxWxD):

Minimum distance above an electric hob: 430
Minimum distance above a gas hob: 650
Net weight (kg): 8.611
Type of control: mechanical
Number of speed settings: 2
Maximum output air extraction (m3/h): 328

182 Maximum output recirculating air (m3/h): Number of lights (Stck): 2 64 Noise level (dB(A) re 1 pW): Diameter of air outlet (mm): 120 / 150 Grease filter material: Washable aluminium EAN code: 4242005231942 Connection rating (W): 93 Current (A): 10

Voltage (V): 220-240
Frequency (Hz): 50
Plug type: GB plug
Installation type: Built-in





### Serie | 2, Telescopic cooker hood, 60 cm, Silver metallic DFM063W56B

# Telescopic cooker hoods extend when in use and slide neatly away when not in operation.

#### **Features**

- Rocker switch control for extractor speeds and light
- Automatic On/Off operation when telescopic canopy is pulled out and pushed back
- Capacitor motor
- 2 power levels
- 2 x 1,5W LED
- 2 removable metal grease filter cassettes

#### Design

- 60 cm wide
- Silver metallic lacquer
- Handle strip specification: stainless steel with logo
- Filter cover stainless steel, perforated and dishwasher safe

#### Performance


- Suitable for ducted or recirculating operation
- For recirculated extraction recirculating kit (accessory)
- Energy Efficiency Class: C (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 max. 328 m<sup>3</sup>/h
- Noise level according to EN 60704-2-13 at max.normal use exhaust air:64 dB(A)re 1 pW(A)re 1 pW
- Colour Temperature: 3500 K
- Light Intensity: 131 lux
- Power rating: 93 W
- Average Energy Consumption: 41.1 kWh/year\*
- Blower Efficiency Class: D\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*


### Planning and installation information

- Dimensions (HxWxD): 203 x 598 x 290 mm
- Built-in dimensions (HxWxD): 162 x 526 x 290 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Electrical cable length 1.75 m
- \* In accordance with the EU-Regulation No 65/2014





## Serie | 2, Telescopic cooker hood, 60 cm, Silver metallic DFM063W56B







Depth of the filter drawer can be adjusted by up to 29 mm measurements in mm











# Serie | 2, Telescopic cooker hood, 60 cm, Silver metallic DFM063W56B

