

**Serie | 4, Island cooker hood, 90 cm,
clear glass
DIG97IM50B**

B



Stylish island chimney hoods perfectly complement island hob installations.

- An impressive extraction rate of 732 m³/h ensures this hood will have your kitchen odour free in no time.
- **TouchSelect control:** quick touch-control selection of desired settings and light.
- **Silent:** maximum extractor performance with little noise
- **High grease filtration level:** filters up to 86.1% of the grease from the kitchen air.

Technical Data

| | |
|---|--------------------|
| Color chimney : | Stainless steel |
| Typology : | Chimney |
| Approval certificates : | CE, VDE |
| Length of electrical supply cord (cm) : | 130 |
| Height of the chimney (mm) : | 691-871/691-991 |
| Height of product, without chimney (mm) : | 53 |
| Net weight (kg) : | 30.088 |
| Type of control : | Electronic |
| Maximum output air extraction (m ³ /h) : | 429 |
| Boost position output recirculating (m ³ /h) : | 384 |
| Maximum output recirculating air (m ³ /h) : | 315 |
| Boost position air extraction (m ³ /h) : | 732 |
| Number of lights (Stck) : | 4 |
| Noise level (dB(A) re 1 pW) : | 60 |
| Diameter of air outlet (mm) : | 120 / 150 |
| Grease filter material : | Washable aluminium |
| EAN code : | 4242005099283 |
| Connection rating (W) : | 256 |
| Current (A) : | 10 |
| Voltage (V) : | 220-240 |
| Frequency (Hz) : | 50; 60 |
| Plug type : | GB plug |
| Installation type : | Island |

Optional accessories

- DHZ1230 : Adapter for roof inclination left/right
- DHZ1240 : Adapter for roof inclination front/back
- DHZ1245 : Chimney extension 1100 mm
- DHZ1255 : Chimney extension 1600 mm
- DHZ5326 : Active carbon filter
- DHZ5365 : Recirculating kit
- DSZ5201 : CleanAir active carbon filter spare part
- DSZ6220 : CleanAir Recirculation Kit
- DZZ0XX0P0 : CleanAir act.carbon filter regenerative



Serie | 4, Island cooker hood, 90 cm, clear glass DIG97IM50B

Stylish island chimney hoods perfectly complement island hob installations.

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A++ to E)*
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 429 m³/h
Intensive 732 m³/h
- Noise max. Normal Level: 60 dB*

Special features

- TouchControl with Electronic display
- 3 power levels & intensive setting
- 4 x 1.5W LED light
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 2 removable metal grease filter cassettes
- easy to clean Inner frame

Design

- Brushed steel
- Glass design
- Clear glass
- Island chimney hood
- Designed for ceiling mounted installation
- TouchControl
- Electronic control

Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 429 m³/h
Intensive 732 m³/h
- Extraction rate according to EN 61591 max. 429 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 60 dB(A) re 1 pW (47 dB(A) re 20 µPa sound pressure)
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 60 dB(A) re 1 pW (47 dB(A) re 20 µPa sound pressure)
Intensive: 71 dB(A) re 1 pW (58 dB(A) re 20 µPa sound pressure)
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 60 dB (A) re 1pW
- Noise max. Normal Level: 60 dB*
- Power rating: 256 W
- Light Intensity: 502 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe ø 150 mm (ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating (HxWxD): 744-1044 x 898 x 600 mm
- Dimensions recirculating with CleanAir module (HxWxD): 812-1044 x 898 x 600 mm
- Energy Efficiency Class: B (at a range of energy efficiency classes from A++ to E)*
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 71.3 kWh/year*

Optional accessories

- Recirculating kit

* In accordance with the EU-Regulation No 65/2014

Serie | 4, Island cooker hood, 90 cm, clear glass
DIG97IM50B

