

**Serie | 6, ceiling cooker hood, 105 cm,  
White  
DRR16AQ20**



**The Plug&Play ceiling ventilation: for a  
simple and space-saving solution, with  
perfect installation in open plan kitchens.**

- For fast and effective extraction, the intensive speed setting removes strong kitchen odours quickly and effectively.
- For fast and effective extraction, the intensive speed setting removes strong kitchen odours quickly and effectively.

**Technical Data**

Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	0
Minimum distance above an electric hob :	650
Minimum distance above a gas hob :	650
Net weight (kg) :	33.873
Type of control :	Electronic
Number of speed settings :	3-stage + 2 intensive
Boost position output recirculating (m3/h) :	580.0
Number of lights :	4
Grease filter material :	Washable stainless steel
EAN code :	4242005098804
Connection Rating (W) :	172
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	no plug
Installation typology :	Island



4 242005 098804

## Serie | 6, ceiling cooker hood, 105 cm, White DRR16AQ20

**The Plug&Play ceiling ventilation: for a simple and space-saving solution, with perfect installation in open plan kitchens.**

---

### **Key performance features:**

- Energy Efficiency Class: "blank" (at a range of energy efficiency classes from A+++ to D)

### **Special features**

- 3 power levels and 2 intensive settings
- Colour Temperature: 3500 K
- Softlight dimmer function
- Automatic after running (10 min)
- Automatic intensive revert (6mins)
- 3 metal grease filter cassettes
- Saturation indicator for metal and charcoal filter

### **Design**

- Electronic control
- Designed for ceiling mounted installation
- 4 x 3W LED lights
- Steel filter cover

### **Performance/technical information**

- Suitable for recirculated extraction
- For recirculated extraction charcoal filter (accessory) needed
- Extraction rate in recirculation mode with Clean Air Plus odor filter: Max. normal use: 409 m<sup>3</sup>/h Intensive: 580 m<sup>3</sup>/h Noise level in recirculation mode with Clean Air Plus odor filter : Max. normal use: 68 dB(A) re 1 pW Intensive: 76 dB(A) re 1 pW
- Light Intensity: 505 lux
- Electrical cable length 0 m
- Dimensions recirculating (HxWxD): 183-183 x 1050 x 600 mm
- Lighting Efficiency Class: A\*

*\* In accordance with the EU-Regulation No 65/2014*