

**Serie | 2**
**DWG64BC50B**

**Glass design  
Chimney extractor hood  
Brushed steel  
60 cm wide**



**Hood with glass design: performance combined with straight glass design matching your kitchen.**

- **Push buttons:** simply change the desired power level settings with mechanic control.
- An impressive extraction rate of 340 m<sup>3</sup>/h ensures this hood will have your kitchen odour free in no time.
- **Silent:** maximum extractor performance with little noise


**Technical Data**

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length of electrical supply cord (cm) :	130
Height of the chimney (mm) :	576-906/576-998
Height of product, without chimney (mm) :	59
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	12.3
Type of control :	mechanical
Number of speed settings :	3
Maximum output air extraction (m <sup>3</sup> /h) :	340
Maximum output recirculating air (m <sup>3</sup> /h) :	180
Number of lights (Stck) :	2
Noise level (dB(A) re 1 pW) :	64
Diameter of air outlet (mm) :	150 / 120
Grease filter material :	Washable aluminium
EAN code :	4242005051151
Connection rating (W) :	100
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	GB plug
Installation type :	Wall-mounted

**Optional accessories**

- DHZ1225 : Chimney extension 1000 mm
- DHZ1235 : Chimney extension 1500 mm
- DHZ6550 : Brushed steel back panel
- DHZ6551 : Brushed steel back panel
- DSZ5201 : CleanAir active carbon filter spare part
- DSZ6200 : CleanAir Recirculation Kit
- DWZ0DX0A0 : Active carbon filter
- DWZ0DX0U0 : Recirculating kit
- DZZ0XX0P0 : CleanAir act.carbon filter regenerative



**Serie | 2 Hoods****DWG64BC50B**

**Glass design**  
**Chimney extractor hood**  
**Brushed steel**  
**60 cm wide**

**Hood with glass design: performance combined with straight glass design matching your kitchen.**

**Key performance features:**

- Energy Efficiency Class: D (at a range of energy efficiency classes from A++ to E)\*
- Max. extraction rate: 340 m<sup>3</sup>/h
- Noise max. Normal Level: 64 dB\*

**Features**

- Push button control
- 3 power levels
- 2 x 1.5W LED light
- Colour Temperature: 3500 K
- 1 removable metal grease filter cassette
- Designed for wall mounted installation

**Design**

- Brushed steel
- Glass design
- Chimney extractor hood
- Mechanical

**Performance/technical information**

- Suitable for ducted or recirculating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Max. extraction rate: 340 m<sup>3</sup>/h
- Maximum extraction rate exhaust air 340 m<sup>3</sup>/h according to EN 61591
- Extraction rate in recirculation mode:  
Max. normal use: 180 m<sup>3</sup>/h
- Noise max. Normal Level: 64 dB\*
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 64 dB(A) re 1 pW (52 dB(A) re 20 µPa sound pressure)
- Noise level in recirculation mode:  
Max. normal use: 66 dB(A) re 1 pW (54 dB(A) re 20 µPa sound pressure)
- Power rating: 100 W
- Light Intensity: 110 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 635-965 x 600 x 525 mm
- Dimensions recirculating (HxWxD): 635-1075 x 600 x 525 mm
- Dimensions recirculating with CleanAir module (HxWxD):  
703 x 600 x 525 mm - mounting with outer chimney  
833-1163 x 600 x 525 mm - mounting with telescopic chimney
- Energy Efficiency Class: D (at a range of energy efficiency classes from A++ to E)\*
- Blower Efficiency Class: E\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*
- Average Energy Consumption: 54 kWh/year\*

**Optional accessories**

- Recirculating kit

\* In accordance with the EU-Regulation No 65/2014

Serie | 2 Hoods

**DWG64BC50B**

**Glass design**

**Chimney extractor hood**

**Brushed steel**

**60 cm wide**

