

**Serie | 2, wall-mounted cooker hood,
80 cm, Black
DWK87EM60B**



B

- **Intensive speed setting:** removes strong kitchen odours quickly and effectively.
- **Intensive speed setting:** removes strong kitchen odours quickly and effectively.

Technical Data

Typology :	Chimney
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	484-770/554-830
Height of product, without chimney (mm) :	296
Minimum distance above an electric hob :	450
Minimum distance above a gas hob :	600
Net weight (kg) :	14.920
Type of control :	Electronic
Maximum output air extraction (m ³ /h) :	399
Boost position output recirculating (m ³ /h) :	398.0
Boost position air extraction (m ³ /h) :	669
Number of lights :	2
Noise level (dB(A) re 1 pW) :	60
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable aluminium
EAN code :	4242005199730
Connection Rating (W) :	255
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	GB plug
Installation typology :	Wall-mounted

Optional accessories

- DHZ1225 : Chimney extension 1000 mm
- DHZ1235 : Chimney extension 1500 mm
- DHZ5276 : Standard odor filter (replacement)
- DHZ9550 : Brushed steel back panel
- DHZ9551 : Brushed steel back panel
- DWZ0XX0J0 : Long Life recirculation kit
- DWZ1EK1U1 : Standard recirculation kit
- DZZ0XX0P0 : Long Life odor filter (replacement)



Serie | 2, wall-mounted cooker hood, 80 cm, Black DWK87EM60B

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm: max. Normal use 399 m³/h Intensive 669 m³/h
- Noise max. Normal Level: 60 dB*
- TouchControl with Electronic display
- Electronic display
- 3 power levels & intensive setting
- 2 x 1.5W LED light
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 2 metal grease filter cassettes
- Designed for wall mounted installation
- Rim ventilation

Design

- Chimney extractor hood
- TouchControl
- Electronic control

Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 max. 399 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 60 dB (A) re 1pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 60 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air: Max. normal use: 60 dB(A) re 1 pW Intensive: 69 dB(A) re 1 pW
- Extraction rate in recirculation mode: Max. normal use: 320 m³/h Intensive: 398 m³/h
- Noise levels in recirculation mode: Max. normal use: 69 dB(A) re 1 pW Intensive: 74 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches: Extraction rate in recirculation mode: Max. normal use: 349 m³/h Intensive: 474

m³/h Noise level in recirculation mode: Max. normal use: 69 dB(A) re 1 pW Intensive: 76 dB(A) re 1 pW

- Light Intensity: 114 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 780-1066 x 800 x 434 mm
- Dimensions recirculating (HxWxD): 850-1126 x 800 x 434 mm
- Dimensions recirculating with CleanAir module (HxWxD): 956 x 800 x 434 mm - mounting with outer chimney 1016-1306 x 800 x 434 mm - mounting with telescopic chimney
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 59.4 kWh/year*

* In accordance with the EU-Regulation No 65/2014