

iQ700 EX975LVV1E Induction Hob Stainless Steel side trim with bevelled front edge 912 mm



Siemens flexInduction cooktop is designed for greater flexibility when cooking

- ✓ Extra-large cooking surfaces allow for tailored cooking zones, place your cookware wherever you want on the flexInduction cooking zone.
- ✓ Space for extra-large pots and pans thanks to the extendable 32 cm three-ring cooking zone.
- ✓ powerMove Plus enables intuitive control thanks to three heating zones with different temperatures, just by moving the pan
- ✓ dual lightSlider lets you easily and intuitively operate the hob.
- ✓ Home Connect: Information about your hob, no matter where you are - with the easy-to-use Home Connect App.
- ✓ The convenient cookConnect system allows you to control different functions of the extractor hood directly from your cooktop. (with matching hood)
- ✓ The fryingSensor plus controls the temperature in the pan

Features

Technical Data

Product name/family : Cooking zone ceramic
 Construction type : Built-in
 Energy input : Electric
 Total number of positions that can be used at the same time : 5
 Required niche size for installation (HxWxD) : 51 x 880-880 x 490-500
 Width of the product (mm) : 912
 Dimensions of the product (mm) : 51 x 912 x 520
 Dimensions of the packed product (HxWxD) (mm) : 126 x 1073 x 603
 Net weight (kg) : 20.842
 Gross weight (kg) : 23.0
 Residual heat indicator : Separate
 Location of control panel : Hob front
 Basic surface material : Ceramic
 Color of surface : Alu, brushed, Black
 Color of frame : Alu, brushed
 Approval certificates : AENOR, CE
 Length of electrical supply cord (cm) : 110
 EAN code : 4242003759783
 Electrical connection rating (W) : 11100
 Voltage (V) : 220-240
 Frequency (Hz) : 60; 50

Optional accessories

HZ390522	Griddle Plate
HZ390512	Teppan Yaki (large)
HZ390230	System pan diameter 21cm
HZ390012	Steaming Rack for Stainless Steel roaste
HZ390011	Stainless Steel roaster with glas lid



iQ700
EX975LVV1E Induction Hob
Stainless Steel side trim with bevelled
front edge
912 mm

Features

Control:

- Dual lightSlider
- fryingSensor plus with 5 temperature settings

Special features

- Triple ring zone, 2 flexInduction zones
- 5 induction cooking zones
- HomeConnect - enables Remote Monitoring and Control through mobile application
- cookConnect - hood control (with Wi-Fi enabled hood)
- powerMove plus
- reStart function
- Timer for all zones
- Acoustic signal
- Count up timer
- Keep warm function
- 17 power levels
- Power boost setting
- panBoost
- Energy Consumption Display

Safety Features

- Automatic pan recognition
- Automatic safety switch off
- Control panel lock
- Control panel pause
- 2 stage residual heat indicators
- Main on/off switch

Power and size:

- Cooking zones: 1 x Ø 400 mmx230 mm, 3.3 KW (max. Power levels 3.7 KW) Induction or 2 x Ø 200 mm, 2.2 KW (max. Power levels 3.7 KW) Induction; 1 x Ø 400 mmx230 mm, 3.3 KW (max. Power levels 3.7 KW) Induction or 2 x Ø 200 mm, 2.2 KW (max. Power levels 3.7 KW) Induction

Technical information

- Installation measurements: 880 mmx490 mm
- Connection cable (1.1 M)
- Min. worktop thickness: 30 mm
- Connected load: 11.1 kW
- Cable included in packaging

iQ700
 EX975LVV1E Induction Hob
 Stainless Steel side trim with bevelled
 front edge
 912 mm

Dimensioned drawings

