

N 50, Ceiling cooker hood, 90 cm, Stainless steel  
195CAP6N1B



COOKING PASSION SINCE 1877



B



- ✓ Dimmer Function – dim the LED light conveniently with the button on the remote control
- ✓ Remote Control – comfortably control the ceiling hood with a remote
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ Interval Ventilation – automatically ventilates every hour for crisp, clean air

#### Features

##### Technical Data

Approval certificates : NEMKO  
Length of electrical supply cord (cm) : 130  
Required niche size for installation (HxWxD) : 195mm x 410.0mm x 410mm  
Height of product, without chimney (mm) : 60  
Minimum distance above an electric hob : 650  
Minimum distance above a gas hob : 900  
Net weight (kg) : 15.600  
Type of control : Electronic  
Maximum output air extraction (m<sup>3</sup>/h) : 400  
Boost position output recirculating (m<sup>3</sup>/h) : 588.0  
Maximum output recirculating air (m<sup>3</sup>/h) : 423  
Boost position air extraction (m<sup>3</sup>/h) : 690  
Number of lights (Stck) : 4  
Noise level (dB(A) re 1 pW) : 65  
Diameter of air outlet (mm) : 150  
Grease filter material : Washable aluminium  
EAN code : 4242004246442  
Connection rating (W) : 284  
Current (A) : KSA  
Voltage (V) : 220-240  
Frequency (Hz) : 50  
Plug type : GB plug  
Installation type : Island

#### Optional accessories

Z52|CB1X1 Clean Air Standard odor filter (repl.)  
Z52|XC1N1 Clean Air Standard recirc. kit ext. inox  
Z52|XC1W1 Clean Air Stand. recirc. kit ext. white



4 242004 246442

## Features

### Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591  $\varnothing$  15 cm: max. Normal use 400 m<sup>3</sup>/h Intensive 690 m<sup>3</sup>/h
- Noise max. Normal Level: Noise, max. speed in normal us: 65 dB dB\*

### Features

- 3 speeds plus intensive
- Automatic intensive revert (4 mins)
- softLight with dimmer function
- Interval operation
- Automatic after running (Automatic after running (10 minutes))
- Infrared remote control
- 2 metal grease filter cassettes
- Saturation indicator for metal and charcoal filter
- easy to clean Inner frame

### Design

- Electronic controls
- LED display
- Rim ventilation
- metal grease filter
- For ceiling mounted installation

### Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction CleanAir recirculating kit (accessory) needed
- Max. extraction rate: 690 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 65 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air: Max. normal use: 65 dB(A) re 1 pW Intensive: 73 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 65 dB (A) re 1pW
- With the Clean Air Standard recirculation kit (available as optional accessory) your appliances reaches: Extraction rate in recirculation mode: Max. normal use: 423 m<sup>3</sup>/h Intensive: 588 m<sup>3</sup>/h Noise level in recirculation mode with Clean Air Standard odor

filter : Max. normal use: 69 dB(A) re 1 pW Intensive: 74 dB(A) re 1 pW

- Power rating: 284 W
- Light Intensity: 366 lux
- Electrical cable length 1.3 m
- Diameter pipe  $\varnothing$  150 mm ( $\varnothing$  150 mm enclosed)
- Dimensions exhaust air (HxWxD): 193-193 x 900 x 440 mm
- Blower Efficiency Class: B\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*
- Average Energy Consumption: 62.6 kWh/year\*

\* In accordance with the EU-Regulation No 65/2014

Dimensioned drawings

