

Serie | 6, Built-in fridge-freezer with freezer at bottom, 177.2 x 55.8 cm KIS87AFE0G











Included accessories

3 x egg tray 1 x ice cube tray 1 x bottle holder in door tray

Optional accessories

KSZ10020 : Bottle Rack

The bottom freezer with VitaFresh plus drawer: keeps your fruit and vegetables fresher for longer.

- LED lights bring a completely new lighting concept to fridges
- VarioZone: more flexibility due to variable-use glass shelves and drawers in the freezer compartment.
- Automatic super freezing: for freezing smaller food loads faster whilst protecting your frozen items from defrosting, thanks to the detection of temperature increase
- BigBox frozen food drawer: for stacking storage containers or for large frozen food items.
- EasyAccess Shelf: retractable glass shelf for convenient loading and unloading and a perfect view.

Technical Data

A ↑ G

Energy Efficiency Class (Regulation (EU) 2017/1369):	Ε		
Average annual energy consumption in kilowatt hour per year			
(kWh/a) (EU) 2017/1369:	207		
Sum of volume of frozen compartments (EU 2017/1369):	63		
Sum of volume of chill compartments (EU 2017/1369):	209		
Airborne acoustical noise emissions (EU 2017/1369):	36		
Airborne acoustical noise emission class (EU 2017/1369):	С		
Construction type:	uilt-in		
Door panel options: Not pos	sible		
Width of the appliance:	558		
Depth of the product:	545		
Required niche size for installation (HxWxD):			

1775.0 x 560 x 550

Net weight (kg): 62,207 Connection rating (W): 90 Current (A): 13 Door hinge: Right reversible Voltage (V): 220-240 Frequency (Hz): 50 CE, G-Mark, VDE Approval certificates: Length of electrical supply cord (cm): 230 Storage Period in Event of Power Failure (h): 12 Number of compressors: 1 Number of independent cooling systems: 2 Interior ventilator: No Reversible Door Hinge: Yes Number of Adjustable Shelves in fridge compartment (Stck): Shelves for Bottles: Frost free system: No Installation type: Full-integrated Type of hinge: Flush-folding





Serie | 6, Built-in fridge-freezer with freezer at bottom, 177.2 x 55.8 cm KIS87AFE0G

The bottom freezer with VitaFresh plus drawer: keeps your fruit and vegetables fresher for longer.

Functions

- Bright interior LED fridge light

Design features

- Electronic control for fridge and freezer with LED display
- FreshSense Constant temperature control by intelligent sensor technology
- Two separate cooling circuits allow independent temperature control and prevents the transference of humidity between the fridge and freezer cavity
- Super Cooling: automatic deactivation
- SuperFreeze function with automatic deactiviation
- Holiday mode
- Optical and acoustical door open warning

Design features

- 5 safety glass shelves (4 height adjustable)
- 5 door trays, including 1x dairy compartment

Freshness System

- 1 VitaFresh Plus drawer with humidity control. Fruit and vegetables retain vitamins and last longer.

Food freshness system

- LowFrost less ice creation and therefore quicker defrosting
- Vario Zone removable safety glass shelves for extra space!
- 2 transparent freezer drawers, including 1 BigBox

Dimension and installation

- Dimensions: 177.2 cm H x 55.8 cm W x 54.5 cm D
- Niche Dimensions: 177.5 cm H x 56 cm W x 55 cm D

Key features - Fridge section

- Right hinged door, door reversible
- Connection value 90 W
- **-** 220 240 V
- Transportation handles

Key features - Freezer section

- KIS87AFE0G
- bottle holder in door tray

Country Specific Options

- Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.

Design features

Dimension and installation


Additional features


Performance and Consumption


- EU19_EEK_D: E
- Total Volume: 272 l
- Net Fridge Volume : 209 INet Freezer Volume : 63 I
- Freezing capacity 24h : 5 kg
- Annual Energy Consumption: 207 kWh/a
- Climate Class: SN-ST
- Noise Level: 36 dB
- Temperature rise time : EU19_Temperature rise time_D: 12 H



Serie | 6, Built-in fridge-freezer with freezer at bottom, 177.2 x 55.8 cm KIS87AFE0G








The specified unit door dimensions are valid for a door gap of 4 mm.


measurements in mm

measurements in mm
Recommended gap dimensions for flat hinges



F	R	X
16-19	0-3	2.5
20	0-1	3
	2-3	2.5
21	0-1	3
	2-3	2.5
22	0	4
	1	3.5
	2-3	3

The gap dimensions recommended in the table must be adhered to in order to ensure that appliance doors do not collide with anything when they are opened, and to avoid causing damage to kitchen units.



Maximal permissible weight of the unit fronts

Fitted unit fronts that exceed the permissible weight may cause damage and result in functional impairment

of the hinge Weight

A: Appliance door height including hinges in

3: Undamped hinge, unit front in 5: Damped hinge, unit front in kg

A	В	С
1500-1750	22	22
720-1400	19	19
A1	15	19