

iQ500
Canopy hood
LB78574GB stainless steel



The powerful canopy cooker hood is concealed above the cooktop.

- ✓ The 730 m³/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ When required the intensive setting temporarily increases the extraction rate, with automatic revert after 6 min.
- ✓ At 52 dB the hood is extremely quiet when being used.

Features

Technical Data

Typology : Traditional
 Approval certificates : CE, VDE
 Length of electrical supply cord (cm) : 150
 Required niche size for installation (HxWxD) : 418mm x 676mm x 264mm
 Minimum distance above an electric hob : 500
 Minimum distance above a gas hob : 650
 Net weight (kg) : 10.0
 Type of control : Electronic
 Maximum output air extraction (m³/h) : 630
 Boost position output recirculating (m³/h) : 310
 Maximum output recirculating air (m³/h) : 300
 Boost position air extraction (m³/h) : 730
 Number of lights (Stck) : 2
 Noise level (dB(A) re 1 pW) : 66
 Diameter of air outlet (mm) : 120 / 150
 Grease filter material : Washable aluminium
 EAN code : 4242003686263
 Connection rating (W) : 277
 Current (A) : 3
 Voltage (V) : 220-240
 Frequency (Hz) : 50
 Plug type : GB plug
 Installation type : Built-in



Optional accessories

- | | |
|---------|-------------------------------|
| LZ55750 | Recirculating kit |
| LZ55651 | Active carbon filter |
| LZ46830 | CleanAir Recirculation Kit |
| LZ46810 | CleanAir active carbon filter |

iQ500

Canopy hood

LB78574GB stainless steel

Features

Design

- 70 cm wide
- stainless steel
- White electronic display
- Electronic control via Soft touch button control
- Light colour: warm white
- For installation in a kitchen cabinet
- Designed for suspended or flush ceiling installation

Key features

- Soft touch button control for extractor speeds and light
- 2 x 1W LED lights
- 2 x metal grease filter cassettes
- Steel filter cover, Steel filter cover
- Rim ventilation

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction charcoal filter (accessory) needed
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 630 m³/h
Intensive 730 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 66 dB(A) re 1 pW (52 dB(A) re 20 µPa sound pressure)
Intensive: 69 dB(A) re 1 pW (55 dB(A) re 20 µPa sound pressure)
- 3 x power levels plus intensive setting
- Power rating: 277 W
- Automatic intensive revert
- Noise max. Normal Level: 66 dB*
- Extractor hose 120 mm
- Dimensions (WxD): 700 x 300 mm
- built-in dimensions (HxWxD): 418 x 676 x 264 mm
- Dimensions exhaust air (HxWxD): 418-418 x 700 x 300 mm
- Diameter pipe ø 150 mm (ø 120 mm enclosed)
- Light Intensity: 244 lux
- Colour Temperature: 4000 K
- Average Energy Consumption: 105.7 kWh/year*
- Energy Efficiency Class: C*
- Blower Efficiency Class: C*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: D*

* In accordance with the EU-Regulation No 65/2014