

iQ300
LC87KHM60B
Angled design
Chimney hood
Black
80 cm

A



Angled extractor hood with outstanding design and high extraction rate for a powerful performance.

- ✓ The powerful motor with an high extraction rate of 680 m³/h for fresh air in your kitchen.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ When required the intensive setting temporarily increases the extraction rate, with automatic revert after 6 min.
- ✓ At 56 dB the hood is especially quiet when being used.

Features

Technical Data

Color chimney : Stainless steel
 Typology : Chimney
 Approval certificates : CE, VDE
 Length of electrical supply cord (cm) : 130
 Height of product, without chimney (mm) : 323
 Minimum distance above an electric hob : 450
 Minimum distance above a gas hob : 600
 Net weight (kg) : 20.0
 Type of control : Electronic
 Maximum output air extraction (m³/h) : 420
 Boost position output recirculating (m³/h) : 570
 Maximum output recirculating air (m³/h) : 380
 Boost position air extraction (m³/h) : 680
 Number of lights (Stck) : 2
 Noise level (dB(A) re 1 pW) : 56
 Diameter of air outlet (mm) : 120 / 150
 Grease filter material : Washable aluminium
 EAN code : 4242003761007
 Connection rating (W) : 263
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 50; 60
 Plug type : GB plug
 Installation type : Wall-mounted



Optional accessories

LZ56200 : CleanAir active carbon filter spare part , LZ10AXL50 : Chimney extension 1500 mm , LZ10AXK50 : Chimney extension 1000 mm , LZ10AKU00 : Recirculation kit , LZ10AKT00 : Recirculation kit for chimless use , LZ10AKS00 : Recirculation kit regenerative , LZ10AKR00 : Recirculation kit regenerative chimless , LZ10AKA00 : Active carbon filter (spare part) , LZ00XXP00 : CleanAir act.carbon filter regenerative

iQ300
LC87KHM60B
Angled design
Chimney hood
Black
80 cm

Features

Key performance features:

- Energy Efficiency Class: A*
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 420 m³/h
Intensive 680 m³/h
- Noise max. Normal Level: 56 dB*

Features

- 3 x power levels plus intensive setting
- 2 x 3W LED
- Colour Temperature: 3500 K
- Twin channel high performance fan motor
- Automatic intensive revert (6mins)
- 2 x metal grease filter cassettes
- easy to clean Inner frame
- For wall mounted installation
- Rim ventilation

Design

- Black glass

Angled design

- Chimney hood
- Touch control for extractor speeds and light
- Electronic control

Performance/technical information

- Suitable for ducted and re-circulating operation
- In recirculation operation chimless use possible
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Easy installation system
- Max. extraction rate: 680 m³/h
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 420 m³/h
Intensive 680 m³/h
- Extraction rate in recirculation mode:
Max. normal use: 380 m³/h
Intensive: 570 m³/h
- Noise max. Normal Level: 56 dB*
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 56 dB(A) re 1 pW (42 dB(A) re 20 µPa sound pressure)
Intensive: 65 dB(A) re 1 pW (51 dB(A) re 20 µPa sound pressure)
- Noise levels in recirculation mode:
Max. normal use: 65 dB(A) re 1 pW (51 dB(A) re 20 µPa sound pressure)
Intensive: 75 dB(A) re 1 pW (61 dB(A) re 20 µPa sound pressure)
- Power rating: 263 W
- Light Intensity: 90 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 928-1198 x 790 x 499 mm
- Dimensions recirculating, chimney (HxWxD): 988-1258 x 790 x 499 mm
- Dimensions recirculating, chimless (HxWxD): 452 mm x 790 x 499 mm
- Dimensions recirculating with CleanAir module (HxWxD):
1118 x 790 x 499 mm - mounting with outer chimney
1188-1458 x 790 x 499 mm - mounting with telescopic chimney
- Energy Efficiency Class: A*
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 51 kWh/year*

Optional accessories

- Recirculating kit

* In accordance with the EU-Regulation No 65/2014

iQ300
 LC87KHM60B
 Angled design
 Chimney hood
 Black
 80 cm

Dimensioned drawings

