


iQ300, Island cooker hood, 90 cm, clear glass LF97GBM50B



The island hood features an efficient extraction rate in the distinctive Siemens design.

- ✓ Effective extraction thanks to the powerful motor with a high extraction rate (732 m³/h).
- ✓ LED lights: For optimal visibility and ambience when cooking.
- ✓ Designed to be pleasantly quiet when being used (60 db(A)).
- ✓ The intensive setting temporarily increases the extraction rate when cooking vapour is especially intense, with automatic revert after 6 min.
- ✓ Thanks to touchControl the power level and the LED lights can be selected with ease.

Features

Technical Data

Color chimney : Stainless steel
 Typology : Chimney
 Approval certificates : CE, VDE
 Length of electrical supply cord (cm) : 130
 Height of the chimney (mm) : 698-878/698-998
 Height of product, without chimney (mm) : 46
 Net weight (kg) : 30.088
 Type of control : Electronic
 Maximum output air extraction (m³/h) : 429
 Boost position output recirculating (m³/h) : 384
 Maximum output recirculating air (m³/h) : 315
 Boost position air extraction (m³/h) : 732
 Number of lights (Stck) : 4
 Noise level (dB(A) re 1 pW) : 60
 Diameter of air outlet (mm) : 120 / 150
 Grease filter material : Washable aluminium
 EAN code : 4242003832110
 Connection rating (W) : 256
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 60; 50
 Plug type : GB plug
 Installation type : Island



Optional accessories

LZ57500	cleanAir Recirculation Kit
LZ56200	CleanAir active carbon filter spare part
LZ53650	Recirculating kit
LZ53251	Active carbon filter
LZ12520	Extension for mounting kit 1000 mm
LZ12500	Extension for mounting kit 500 mm
LZ12400	Adapter for roof inclination front/back
LZ12375	Chimney extension 1600 mm
LZ12300	Adapter for roof inclination left/right
LZ12275	Chimney extension 1100 mm
LZ00XP00	CleanAir act.carbon filter regenerative

iQ300, Island cooker hood, 90 cm, clear glass LF97GBM50B

Features

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A++ to E)*
- Extraction rate according to EN 61591 ø 15 cm:
 - max. Normal use 429 m³/h
 - Intensive 732 m³/h
- Noise max. Normal Level: 60 dB*

Features

- touchControl with Electronic display
- 4 x 1.5W LED
- 3 x power levels plus intensive setting
- Automatic intensive revert (6mins)
- Steel filter cover
- 2 x metal grease filter cassettes

Design

- 90 cm
- Stainless Steel
- Stainless steel hood with glass canopy
- For ceiling mounted installation
- Electronic control

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Max. extraction rate: 732 m³/h
- Extraction rate according to EN 61591 ø 15 cm:
 - max. Normal use 429 m³/h
 - Intensive 732 m³/h
- Extraction rate in recirculation mode:
 - Max. normal use: 315 m³/h
 - Intensive: 384 m³/h
- Noise max. Normal Level: 60 dB*
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
 - Max. normal use: 60 dB(A) re 1 pW (47 dB(A) re 20 µPa sound pressure)
 - Intensive: 71 dB(A) re 1 pW (58 dB(A) re 20 µPa sound pressure)
- Noise levels in recirculation mode:
 - Max. normal use: 73 dB(A) re 1 pW (60 dB(A) re 20 µPa sound pressure)
 - Intensive: 77 dB(A) re 1 pW (64 dB(A) re 20 µPa sound pressure)
- Power rating: 256 W
- Light Intensity: 523 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe ø 150 mm (ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating, chimney (HxWxD): 744-1044 x 898 x 600 mm
- Energy Efficiency Class: B (at a range of energy efficiency classes from A++ to E)*
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 71.3 kWh/year*

Optional accessories

- Recirculating kit

* In accordance with the EU-Regulation No 65/2014

iQ300, Island cooker hood, 90 cm,
clear glass
LF97GBM50B

Dimensioned drawings

