N74TD00N0 396 MM









Features

Technical Data

Product name/family : Vario/Domino Teppan Yaki

Construction type: Built-in Energy input: Electric Type of control: Electronic Grill grating material: N/A

Required niche size for installation (HxWxD) : $90 \times x$

Width of the product (mm): 396

Dimensions of the product (mm) : $90 \times 396 \times 546$

Dimensions of the packed product (HxWxD) (mm) : $230 \times 480 \times 610$

Net weight (kg): 10.0 Gross weight (kg): 12.0 Residual heat indicator: Separate Basic surface material: N/A

Color of surface : Stainless steel, Stainless steel

Color of frame : Stainless steel Approval certificates : CE, VDE

Length of electrical supply cord (cm): 100

EAN code : 4242004188117

Electrical connection rating (W): 1900

Current (A): 13 Voltage (V): 220-240 Frequency (Hz): 60; 50

Included accessories

2 x spatula



Optional accessories

Z9914X0 Connecting strip

N74TD00N0 396 MM

Feature

Control

• TouchControl

Flexibility

- Stainless steel cooking surface
- 2 cooking zones

Special features

- Main switch
- Power on indicator light
- Temperature range 140 240 °C
- heating-up control
- Special level for keeping warm (70°C)
- Special level for cleaning (40°C)
- LED display for each zone
- 2 stage residual heat indicators
- Count up timer
- LED timer for each zone with switch off function and acoustic signal
- Control panel suspension
- Safety cut out facility
- Control panel lock
- ReStart function
- Individual energy consumption display
- 2 spatulas included

Design


- Ceramic glass on stainless steel trim
- Removable ceramic glass cover

Technical information

- Installation measurements (mm): 360 x 490-500
- 40 cm
- Length connecting cable 100 cm
- Min. worktop thickness: 30 mm
- Output 1900 W


N74TD00N0 396 MM

Dimensioned drawings



measurements in mm

Domino combination options with corresponding appliance and cut-out dimensions (see table)



When installing several elements side by side. Domino combination options with corresponding appliance and cut-out dimensions

| | A | В | C | D | L | × |
|-------------------|-----|-----|-----|------|------|------|
| 2x30 | 306 | 306 | | 100 | 612 | 576 |
| 1x30, 1x40 | 306 | 396 | | - | 702 | 666 |
| 1x30, 1x60 | 306 | 606 | | - | 912 | 876 |
| 1x30, 1x70* | 306 | 708 | | - | 1014 | 978 |
| 1x30, 1x80 | 306 | 826 | | | 1132 | 1096 |
| 1x30, 1x90 | 306 | 918 | | | 1224 | 1188 |
| 2x40 | 396 | 396 | | | 792 | 756 |
| 1x40, 1x60 | 396 | 606 | | - | 1002 | 966 |
| 1x40, 1x70* | 396 | 708 | | - | 1104 | 1068 |
| 1x40, 1x80 | 396 | 826 | | + | 1222 | 1186 |
| 1x40, 1x90 | 396 | 918 | 4 | - 40 | 1314 | 1278 |
| 3x30 | 306 | 306 | 306 | | 918 | 882 |
| 2x30, 1x40 | 306 | 306 | 396 | | 1008 | 972 |
| 2x30, 1x60 | 306 | 306 | 606 | | 1218 | 1182 |
| 2x30, 1x70* | 306 | 306 | 708 | | 1320 | 1284 |
| 2x30, 1x80 | 306 | 306 | 826 | + | 1438 | 1402 |
| 2x30, 1x90 | 306 | 306 | 918 | | 1530 | 1494 |
| 1x30, 2x40 | 306 | 396 | 396 | | 1098 | 1062 |
| 1x30, 1x40, 1x60 | 306 | 396 | 606 | | 1308 | 1272 |
| 1x30, 1x40, 1x80 | 306 | 396 | 826 | + | 1528 | 1492 |
| 1x30, 1x40, 1x90 | 306 | 396 | 918 | | 1620 | 1584 |
| 3x40 | 396 | 396 | 396 | + | 1188 | 1152 |
| 2x40, 1x60 | 396 | 396 | 606 | | 1398 | 1362 |
| 1x30, 1x40, 1x70° | 306 | 396 | 708 | - | 1410 | 1374 |
| 4x30 | 306 | 306 | 306 | 306 | | 1188 |
| 3x30, 1x40 | 306 | 306 | 306 | 396 | 1314 | 1278 |
| 2x30, 2x40 | 306 | 306 | 396 | 396 | 1404 | 1368 |
| 1x30, 3x40 | 306 | 396 | 396 | 396 | 1494 | 1458 |

^{*} Not possible with 70 cm induction hob